

Connecting via Winsock to STN

Welcome to STN International! Enter x:x

LOGINID:SSSPTA1743BXS

PASSWORD:

TERMINAL (ENTER 1, 2, 3, OR ?):2

* * * * * Welcome to STN International * * * * *

NEWS	1		Web Page for STN Seminar Schedule - N. America
NEWS	2	JAN 08	CHEMLIST enhanced with New Zealand Inventory of Chemicals
NEWS	3	JAN 16	CA/CAPplus Company Name Thesaurus enhanced and reloaded
NEWS	4	JAN 16	IPC version 2007.01 thesaurus available on STN
NEWS	5	JAN 16	WPIDS/WPINDEX/WPIX enhanced with IPC 8 reclassification data
NEWS	6	JAN 22	CA/CAPplus updated with revised CAS roles
NEWS	7	JAN 22	CA/CAPplus enhanced with patent applications from India
NEWS	8	JAN 29	PHAR reloaded with new search and display fields
NEWS	9	JAN 29	CAS Registry Number crossover limit increased to 300,000 in multiple databases
NEWS	10	FEB 15	PATDPASPC enhanced with Drug Approval numbers
NEWS	11	FEB 15	RUSSIAPAT enhanced with pre-1994 records
NEWS	12	FEB 23	KOREAPAT enhanced with IPC 8 features and functionality
NEWS	13	FEB 26	MEDLINE reloaded with enhancements
NEWS	14	FEB 26	EMBASE enhanced with Clinical Trial Number field
NEWS	15	FEB 26	TOXCENTER enhanced with reloaded MEDLINE
NEWS	16	FEB 26	IFICDB/IFIPAT/IFIUDB reloaded with enhancements
NEWS	17	FEB 26	CAS Registry Number crossover limit increased from 10,000 to 300,000 in multiple databases
NEWS	18	MAR 15	WPIDS/WPIX enhanced with new FRAGHITSTR display format
NEWS	19	MAR 16	CASREACT coverage extended
NEWS	20	MAR 20	MARPAT now updated daily
NEWS	21	MAR 22	LWPI reloaded
NEWS	22	MAR 30	RDISCLOSURE reloaded with enhancements
NEWS	23	APR 02	JICST-EPLUS removed from database clusters and STN
NEWS	24	APR 30	GENBANK reloaded and enhanced with Genome Project ID field
NEWS	25	APR 30	CHEMCATS enhanced with 1.2 million new records
NEWS	26	APR 30	CA/CAPplus enhanced with 1870-1889 U.S. patent records
NEWS	27	APR 30	INPADOC replaced by INPADOCDB on STN
NEWS	28	MAY 01	New CAS web site launched
NEWS	29	MAY 08	CA/CAPplus Indian patent publication number format defined
NEWS	30	MAY 14	RDISCLOSURE on STN Easy enhanced with new search and display fields
NEWS	31	MAY 21	BIOSIS reloaded and enhanced with archival data
NEWS	32	MAY 21	TOXCENTER enhanced with BIOSIS reload
NEWS	33	MAY 21	CA/CAPplus enhanced with additional kind codes for German patents
NEWS	34	MAY 22	CA/CAPplus enhanced with IPC reclassification in Japanese patents
NEWS EXPRESS			NOVEMBER 10 CURRENT WINDOWS VERSION IS V8.01c, CURRENT MACINTOSH VERSION IS V6.0c(ENG) AND V6.0Jc(JP), AND CURRENT DISCOVER FILE IS DATED 25 SEPTEMBER 2006.
NEWS HOURS			STN Operating Hours Plus Help Desk Availability
NEWS LOGIN			Welcome Banner and News Items
NEWS IPC8			For general information regarding STN implementation of IPC 8

Enter NEWS followed by the item number or name to see news on that specific topic.

All use of STN is subject to the provisions of the STN Customer agreement. Please note that this agreement limits use to scientific research. Use for software development or design or implementation of commercial gateways or other similar uses is prohibited and may result in loss of user privileges and other penalties.

* * * * * STN Columbus * * * * *

FILE 'HOME' ENTERED AT 14:02:31 ON 24 MAY 2007

=> file caplus compendex inspec

COST IN U.S. DOLLARS

SINCE FILE

TOTAL

ENTRY

SESSION

FULL ESTIMATED COST

0.42

0.42

FILE 'CAPLUS' ENTERED AT 14:03:54 ON 24 MAY 2007

USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.

PLEASE SEE "HELP USAGETERMS" FOR DETAILS.

COPYRIGHT (C) 2007 AMERICAN CHEMICAL SOCIETY (ACS)

FILE 'COMPENDEX' ENTERED AT 14:03:54 ON 24 MAY 2007

Compendex Compilation and Indexing (C) 2007

Elsevier Engineering Information Inc (EEI). All rights reserved.

Compendex (R) is a registered Trademark of Elsevier Engineering Information Inc.

FILE 'INSPEC' ENTERED AT 14:03:54 ON 24 MAY 2007

Compiled and produced by the IET in association WITH FIZ KARLSRUHE

COPYRIGHT 2007 (c) THE INSTITUTION OF ENGINEERING AND TECHNOLOGY (IET)

=> s resonator (p) piezoelectric

PROXIMITY OPERATOR LEVEL NOT CONSISTENT WITH

FIELD CODE - 'AND' OPERATOR ASSUMED 'RESONATOR (P) PIEZOELEC'

PROXIMITY OPERATOR LEVEL NOT CONSISTENT WITH

FIELD CODE - 'AND' OPERATOR ASSUMED 'RESONATOR (P) PIEZOELEC'

L1 8097 RESONATOR (P) PIEZOELECTRIC

=> s l1 and (functional? or derivat? or immobil?) (8w) electrode (8w) surface

L2 3 L1 AND (FUNCTIONAL? OR DERIVAT? OR IMMOBIL?) (8W) ELECTRODE

(8W) SURFACE

=> s l1 and (functional? or derivat? or immobil?) (8w) electrode

L3 12 L1 AND (FUNCTIONAL? OR DERIVAT? OR IMMOBIL?) (8W) ELECTRODE

=> s l1 and (functional? or derivat? or immobil?) (s) electrode (8w) surface

L4 12 L1 AND (FUNCTIONAL? OR DERIVAT? OR IMMOBIL?) (S) ELECTRODE (8W)

SURFACE

=> display l4 1-12 ibib abs

L4 ANSWER 1 OF 12 CAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 2006:1064758 CAPLUS

DOCUMENT NUMBER: 145:413688

TITLE: Measurement method using QCM sensor

INVENTOR(S): Fukushima, Mizue

PATENT ASSIGNEE(S): Citizen Watch Co., Ltd., Japan

SOURCE: Jpn. Kokai Tokkyo Koho, 10pp.

CODEN: JKXXAF

DOCUMENT TYPE: Patent

LANGUAGE: Japanese

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP 2006275864	A	20061012	JP 2005-97302	20050330
PRIORITY APPLN. INFO.:			JP 2005-97302	20050330

AB An electrode is used for the measurement of a target substance in a sample solution whose surface is immobilized with a substrate reactable with specific locations of the target substance on the electrode surface. Substrates having specific reaction different from the previous substrate are immobilized on the surface of mass sensitizing micro particles and a cross linking reagent is added. The method is able to improve the amplitude of the sensor frequency variation due to the adsorption of the target substance of low concentration or small mol. weight

L4 ANSWER 2 OF 12 CAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 2006:838370 CAPLUS

DOCUMENT NUMBER: 145:246828

TITLE: Piezoelectric immunosensors: analytical potentials and outlooks

AUTHOR(S): Ermolaeva, T. N.; Kalmykova, E. N.

CORPORATE SOURCE: Lipetsk State Technical University, Lipetsk, 398060, Russia

SOURCE: Russian Chemical Reviews (2006), 75(5), 397-409

CODEN: RCRVAB; ISSN: 0036-021X

PUBLISHER: Turpion Ltd.

DOCUMENT TYPE: Journal; General Review

LANGUAGE: English

AB A review. The state-of-the-art in the design of piezoelec. immunosensors is analyzed. The anal. conditions, types of immunochem. reactions detected by piezogravimetric sensors and methods for immobilization of bioreceptor mols. on the electrode surface of piezoelec. resonators are considered. Special attention is given to the use of immunosensors for the detection of microorganisms and low- and high-mol.-mass compds. in liquid media. The bibliog. includes 172 refs.

REFERENCE COUNT: 175 THERE ARE 175 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L4 ANSWER 3 OF 12 CAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 2006:647894 CAPLUS

DOCUMENT NUMBER: 145:194910

TITLE: Using a piezoelectric flow immunosensor for determining sulfamethoxazole in environmental samples

AUTHOR(S): Melikhova, E. V.; Kalmykova, E. N.; Eremin, S. A.; Ermolaeva, T. N.

CORPORATE SOURCE: Lipetsk State Technical University, Lipetsk, 398600, Russia

SOURCE: Journal of Analytical Chemistry (2006), 61(7), 687-693

CODEN: JACTE2; ISSN: 1061-9348

PUBLISHER: Pleiades Publishing, Inc.

DOCUMENT TYPE: Journal

LANGUAGE: English

AB A mass-sensitive piezoelec. flow immunosensor to determine sulfo prepns. in liquid media is proposed. This sensor is equipped with a piezoelec. quartz resonator with Ag electrodes on the silanized surface of which sulfamethoxazole-protein conjugates were immobilized. Antibody binding consts. with conjugate sulfamethoxazole were determined; the most active complementary pairs were chosen. Selectivity of determining sulfamethoxazole in the presence of

its structural analogs was evaluated based on cross-reaction percentages. A procedure for flow-injection determination of sulfamethoxazole was developed using

the piezoelec. immunosensor as a detector; the detection limit of sulfamethoxazole was 0.15 ng/mL. The procedure was tested by determining sulfamethoxazole in soil and natural water.

REFERENCE COUNT: 17 THERE ARE 17 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L4 ANSWER 4 OF 12 CAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1998:661439 CAPLUS
DOCUMENT NUMBER: 129:341418
TITLE: Biosensor.
INVENTOR(S): Tajima, Ichiro; Asami, Osamu
PATENT ASSIGNEE(S): Toyota Central Research and Development Laboratories, Inc., Japan
SOURCE: Jpn. Kokai Tokkyo Koho, 4 pp.
CODEN: JKXXAF
DOCUMENT TYPE: Patent
LANGUAGE: Japanese
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP 10274654	A	19981013	JP 1997-94805	19970328

PRIORITY APPLN. INFO.: JP 1997-94805 19970328

AB The production of new biosensor is described. The system consists of the quartz crystal piezoelec. oscillator, the gold electrode formed on the surface of the crystal, and the functional membrane formed on the surface of electrode, which is bound with antigen or antibody. The electrode is made of at least one of metals, selected from platinum, gold and silver. Antigen or antibody is bound to the functional membrane with covalent bond via organic compound. The immunosensor thus developed is easily prepared and handled, generating the reliable data when applied to the quant. anal. of antibody or antigen.

L4 ANSWER 5 OF 12 CAPLUS COPYRIGHT 2007 ACS on STN

ACCESSION NUMBER: 1986:164644 CAPLUS
DOCUMENT NUMBER: 104:164644
TITLE: Liquid-phase piezoelectric and acoustic transmission studies of interfacial immunochemistry
AUTHOR(S): Thompson, Michael; Arthur, Catherine L.; Dhaliwal, Gurbaksh K.
CORPORATE SOURCE: Dep. Chem., Univ. Toronto, Toronto, ON, M5S 1A1, Can.
SOURCE: Analytical Chemistry (1986), 58(6), 1206-9
CODEN: ANCHAM; ISSN: 0003-2700
DOCUMENT TYPE: Journal
LANGUAGE: English

AB A wide-band marginal oscillator designed to function with mech. damped quartz crystals was used to examine the response of devices with 1 face exposed to stationary and flowing water. The frequency was stable to ± 2 Hz. Monolayer (hydrophobic) and bilayer (hydrophilic) films of stearic acid deposited by Langmuir-Blodgett technol. were used to study the effect of interfacial chemical on shear-wave propagation. Frequency values for the reaction of human IgG and IgA with goat antihuman IgG immobilized to thin films of polyacrylamide gel and directly to the crystal/electrode surface were recorded. The significance of mediation of frequency response by interfacial interactions is discussed.

L4 ANSWER 6 OF 12 COMPENDEX COPYRIGHT 2007 EEI on STN

ACCESSION NUMBER: 2006(28):2924 COMPENDEX
TITLE: Using a piezoelectric flow immunosensor for determining sulfamethoxazole in environmental samples.
AUTHOR: Melikhova, E.V. (Lipetsk State Technical University, Lipetsk, 398600, Russian Federation); Kalmykova, E.N.;

SOURCE: Eremin, S.A.; Ermolaeva, T.N.
Journal of Analytical Chemistry v 61 n 7 July 2006
2006.p 687-693
SOURCE: Journal of Analytical Chemistry v 61 n 7 July 2006
2006.p 687-693
CODEN: JACTE2 ISSN: 1061-9348

PUBLICATION YEAR: 2006
DOCUMENT TYPE: Journal
TREATMENT CODE: Theoretical
LANGUAGE: English

AN 2006(28):2924 COMPENDEX

AB A mass-sensitive piezoelectric flow immunosensor for determining sulfo preparations in liquid media was proposed. This sensor included a piezoelectric quartz resonator with silver electrodes on the silanized surface of which sulfamethoxazole-protein conjugates were immobilized. The binding constants of antibodies with the conjugate sulfamethoxazole were determined, and the most active complementary pairs were chosen. The selectivity of determining sulfamethoxazole in the presence of its structural analogues was evaluated based on the cross reaction percentages. A procedure for the flow-injection determination of sulfamethoxazole was developed using the piezoelectric immunosensor as a detector; the detection limit of sulfamethoxazole was 0.15 ng/mL. The procedure was tested in determining sulfamethoxazole in soil and natural water. \$CPY Pleiades Publishing, Inc., 2006. 17 Refs.

L4 ANSWER 7 OF 12 COMPENDEX COPYRIGHT 2007 EEI on STN

ACCESSION NUMBER: 1980(12):1173 COMPENDEX

DOCUMENT NUMBER: 801293434

TITLE: TEMPERATURE DEPENDENCE OF THE RESONANT FREQUENCY OF ELECTRODED DOUBLY-ROTATED QUARTZ THICKNESS-MODE RESONATORS.

AUTHOR: Tiersten, H.F. (Rensselaer Polytech Inst, Troy, NY); Sinha, B.K.

SOURCE: J Appl Phys v 50 n 12 Dec 1979 p 8038-8051

SOURCE: J Appl Phys v 50 n 12 Dec 1979 p 8038-8051

CODEN: JAPIAU ISSN: 0021-8979

PUBLICATION YEAR: 1979

LANGUAGE: English

AN 1980(12):1173 COMPENDEX DN 801293434

AB A system of approximate equations for the determination of thermal stresses in piezoelectric plates with large thin films of a different material plated on the surfaces is obtained. Conditions resulting in both extensional and flexural stresses are considered and the full anisotropy of the quartz is included in the treatment. The particular case of purely extensional thermal stresses resulting from large electrodes of equal thickness plated on the major surfaces of doubly-rotated quartz thickness-mode resonators is examined in detail. The changes in resonant frequency resulting from the thermally induced biasing stresses and strains are determined from an existing perturbation equation. Calculations, using the newly defined first temperature derivatives of the fundamental elastic constants of quartz, are performed for large gold electrodes on doubly-rotated quartz plates. 25 refs.

L4 ANSWER 8 OF 12 INSPEC (C) 2007 IET on STN

ACCESSION NUMBER: 2000:6622791 INSPEC

DOCUMENT NUMBER: A2000-14-8780B-013; B2000-07-7230J-015

TITLE: Latex piezoelectric immunoassay: it's application for clinical and environmental analysis

AUTHOR: Kurosawa, S.; (Nat. Inst. for Adv. Interdisciplinary Res., Tsukuba, Japan), Muratsugu, M.; Nakamura, C.; Aizawa, H.; Minoura, N.; Miyake, J.; Yoshimoto, M.; Kamo, N.

SOURCE: Proceedings of the 1999 Joint Meeting of the European Frequency and Time Forum and the IEEE International Frequency Control Symposium (Cat. No.99CH36313), vol.2, 1999, p. 1005-8 vol.2 of 2 vol. xxx+1219 pp.; 7 refs.

ISBN: 0 7803 5400 1

Price: 0 7803 5400 1/99/\$10.00

Published by: IEEE, Piscataway, NJ, USA

Conference: Proceedings of the 1999 Joint Meeting of the European Frequency and Time Forum and the IEEE International Frequency Control Symposium, Besancon, France, 13-16 April 1999

Sponsor(s): IEEE Ultrasonics, Ferroelectr. & Frequency Control Soc.; Region de Franche-Comte; Conseil Gen.

Doubs; Ville de Besancon; Bureau Nat. Metrologie (BNM, Paris); Services de l'Etat (Prefecture, DRIRE)

DOCUMENT TYPE: Conference; Conference Article

TREATMENT CODE: Application; Experimental

COUNTRY: United States

LANGUAGE: English

AN 2000:6622791 INSPEC DN A2000-14-8780B-013; B2000-07-7230J-015

AB Latex piezoelectric immunoassay (LPEIA) is a new immunoassay method that requires no immobilization of antigen or antibody on the electrode surface of quartz crystal, in contrast to previous immunoassays in which a piezoelectric crystal is used as a microbalance and immobilization is essential. The frequency change was observed during the aggregation of antibody- or antigen-coated latex particles. This method was used for the detection and is sufficiently sensitive for clinical applications. We made a prototype LPEIA sensor for remote sensing and diagnosis to care for a handicapped person in their home

L4 ANSWER 9 OF 12 INSPEC (C) 2007 IET on STN

ACCESSION NUMBER: 1999:6218644 INSPEC

DOCUMENT NUMBER: A1999-10-8780B-018; B1999-05-7230J-022

TITLE: Thiolated Salmonella antibody immobilization onto the gold surface of piezoelectric quartz crystal

AUTHOR: In-Seon Park; Namsoo Kim (Korea Food Res. Inst., Kyungki, South Korea)

SOURCE: Biosensors & Bioelectronics (1 Nov. 1998), vol.13, no.10, p. 1091-7, 16 refs.

CODEN: BBIOE4, ISSN: 0956-5663

SICI: 0956-5663(19981101)13:10L:1091:TSAI;1-N

Price: 0956-5663/98/\$19.00

Doc.No.: S0956-5663(98)00067-0

Published by: Elsevier, UK

DOCUMENT TYPE: Journal

TREATMENT CODE: Experimental

COUNTRY: United Kingdom

LANGUAGE: English

AN 1999:6218644 INSPEC DN A1999-10-8780B-018; B1999-05-7230J-022

AB An improved antibody-coated sensor system based on quartz crystal microbalance analysis on Salmonella spp. was developed making use of thiolated antibody immobilization onto one gold electrode of the piezoelectric quartz crystal surface. The best results in sensitivity and stability were obtained with the thin layer of a thiol-cleavable, heterobifunctional cross-linker, sulfosuccinimidyl 6-[3-(2-pyridyldithio)propionamido]hexanoate (sulfo-LC-SPDP). The long bridge of this reagent could function as a spacer, facilitating antibody-Salmonella interaction on the gold electrode. After the addition of a S. typhimurium suspension into a reaction cell with 0.1 M sodium phosphate buffer, pH 7.2, the resonant frequency decreased conspicuously. The time required for maximum frequency shift was about 30-90 min. Sensor response was observed for the

microbial suspensions ranging from 9.9×10^5 to 1.8×10^8 CFU/ml

L4 ANSWER 10 OF 12 INSPEC (C) 2007 IET on STN

ACCESSION NUMBER: 1996:5455957 INSPEC

DOCUMENT NUMBER: A1997-03-8780B-004; B1997-02-7510-006

TITLE: A specific microgravimetric immunobiosensor for monitoring insulin concentration

AUTHOR: Suri, C.R.; Mishra, G.C. (Inst. of Microbial Technol., Chandigarh, India)

SOURCE: Proceedings of the First Regional Conference, IEEE Engineering in Medicine and Biology Society and 14th Conference of the Biomedical Engineering Society of India. An International Meet (Cat. No.95TH8089), 1995, p. 4/96-8 of xviii+532 pp., 7 refs.

ISBN: 0 7803 2711 X

Published by: IEEE, New York, NY, USA

Conference: Proceedings of the First Regional Conference, IEEE Engineering in Medicine and Biology Society and 14th Conference of the Biomedical Engineering Society of India. An International Meet, New Delhi, India, 15-18 Feb. 1995

DOCUMENT TYPE: Conference; Conference Article

TREATMENT CODE: Practical; Experimental

COUNTRY: United States

LANGUAGE: English

AN 1996:5455957 INSPEC DN A1997-03-8780B-004; B1997-02-7510-006

AB We have developed a microgravimetric immunobiosensor for the determination of insulin concentration. The system consisted of a modified piezoelectric quartz crystal having bound to its electrode surface an antibody specific to insulin molecules. The antibody to insulin was covalently immobilized on the modified crystal surface via a direct protein A-gold immobilization method using dimethyl pimelimidate (DMP) as the cross linker. The antibody immobilized via the avidin-biotin immobilization method showed low sensitivity and poor stability of the immune biosensor system. Tests of the activity of the resulting immobilized antibody, uniformly oriented using the protein A-gold immobilization method, indicated that surface density close to the theoretical maximum (close packed) was achieved. A comparison between the present study and the well established radioimmunoassay (RIA) revealed that the described microgravimetric immunoassay technique could be developed as a potential alternate to RIA

L4 ANSWER 11 OF 12 INSPEC (C) 2007 IET on STN

ACCESSION NUMBER: 1994:4594225 INSPEC

DOCUMENT NUMBER: A1994-06-8780-012; B1994-03-7230J-008

TITLE: Piezoelectric crystal for the detection of immunoreactions in buffer solutions

AUTHOR: Geddes, N.J.; Paschinger, E.M.; Furlong, D.N.; (Div. of Chem. & Polymers, CSIRO, Clayton, Vic., Australia), Ebara, Y.; Okahata, Y.; Than, K.A.; Edgar, J.A.

SOURCE: Sensors and Actuators B (Chemical) (Jan. 1994), vol.B17, no.2, p. 125-31, 16 refs.

CODEN: SABCEB, ISSN: 0925-4005

Price: 0925-4005/94/\$07.00

DOCUMENT TYPE: Journal

TREATMENT CODE: Experimental

COUNTRY: Switzerland

LANGUAGE: English

AN 1994:4594225 INSPEC DN A1994-06-8780-012; B1994-03-7230J-008

AB The quartz-crystal microbalance (QCM) has been modified to allow for the monitoring of reactions in aqueous solution with about 10 ng sensitivity. This has been achieved by allowing only one electrode to be exposed to the solution of interest, the other being maintained in an air

environment. When the gold electrodes of the QCM are thiol/diimide activated, they can be used to monitor the surface immobilization of immunoglobulin (IgG) molecules and their subsequent interaction with anti-IgG. This is demonstrated by immobilization of sheep or mouse IgG onto the thiolated electrodes, with preference shown for binding with anti-sheep and anti-mouse IgGs, respectively, during subsequent solution interaction. Some cross-reactivity occurs

L4 ANSWER 12 OF 12 INSPEC (C) 2007 IET on STN

ACCESSION NUMBER: 1980:1511447 INSPEC

DOCUMENT NUMBER: A1980-050272; B1980-024131

TITLE: Temperature dependence of the resonant frequency of electroded doubly-rotated quartz thickness-mode resonators

AUTHOR: Tiersten, H.F.; Sinha, B.K. (Dept. of Mech. Engng., Aeronautical Engng. & Mech., Rensselaer Polytechnic Inst., Troy, NY, USA)

SOURCE: Journal of Applied Physics (Dec. 1979), vol.50, no.12, p. 8038-51, 32 refs.

CODEN: JAPIAU, ISSN: 0021-8979

DOCUMENT TYPE: Journal

TREATMENT CODE: Theoretical

COUNTRY: United States

LANGUAGE: English

AN 1980:1511447 INSPEC DN A1980-050272; B1980-024131

AB A system of approximate equations for the determination of thermal stresses in piezoelectric plates with large thin films of a different material plated on the surfaces is derived. The plate equations are obtained by making a suitable expansion of the pertinent variables in the thickness coordinate, inserting the expansion in the appropriate variational principle and integrating with respect to the thickness in the manner of Mindlin. Conditions resulting in both extensional and flexural stresses are considered and the full anisotropy of the quartz is included in the treatment. The particular case of purely extensional thermal stresses resulting from large electrodes of equal thickness plated on the major surfaces of doubly-rotated quartz thickness-mode resonators is treated in detail. The changes in resonant frequency resulting from the thermally induced biasing stresses and strains are determined from an existing perturbation equation. Calculations, using the newly defined first temperature derivatives of the fundamental elastic constants of quartz, are performed for large gold electrodes on doubly-rotated quartz plates

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	9104	resonator same electrode	US- PGPUB; USPAT
2	BRS	L2	30004	(resonator or piezoelectric) same electrode	US- PGPUB; USPAT
3	BRS	L3	199	2 and functional\$9 with electrode near8 surface	US- PGPUB; USPAT
4	BRS	L4	1147	(resonator or piezoelectric) same electrode same protect\$9 near8 (coating or film or layer)	US- PGPUB; USPAT
5	BRS	L5	13	3 and (resonator or piezoelectric) same electrode same protect\$9 near8 (coating or film or layer)	US- PGPUB; USPAT